



Metrotile Shingle



Metrotile[®]
worldwide roofing systems


The unique alternative to traditional shingle and slate

Metrotile Shingle coated steel tiles imitate the look of traditional flat asphalt shingles, but in lightweight, low-maintenance, long-life steel. They are available in different subtle duotone shades. These tiles are designed for use on roofs as well as vertical walls.

It is now possible to achieve a distinctive look without all the problems inherent in traditional asphalt shingles such as delaminating, lifting and general UV damage.

PRODUCT
QUALITY
100%
GUARANTEED

Weatherproof
guarantee
of a
lifetime



Metrotile Shingle

Lightweight high grade steel with Aluzinc® coating for incredible strength and resistance. Suitable for all roof shapes.



Specifications

| | |
|---------------------------|---|
| Minimum pitch | 15° |
| Maximum pitch | 90° |
| Size of tile - overall | 1335 x 300 mm |
| Size of tile - cover | 1235 x 252 mm |
| Gauge of steel | 0.450 mm |
| Linear cover width | 1235 mm |
| Coverage | 0.29 m ² (3.2 tiles per m ²) |
| Weight per m ² | 5.9 kg |
| Weight per tile | 1.75 kg |
| Colours | The available Shingle standard colours are Red-Brown, Black-Brown and Brown-Black, but is also available in Charcoal, Terracotta, Red, Black, Greenstone, Coffee. Also special colours are available to order (ask your dealer for more information). |

Properties



Lightweight

Light and easy to handle and install.



Durable

Colour stability and protects against UV light.



Stable

Resistance to extreme wind or earthquakes.



Strong

Exceptional strength and resistant to damage.



Fire proof

To be conform with the European standards

Installation of the tiles

The tiling battens for installing the shingle tiles have to be positioned with a 250 mm spacing measured from the front batten of each batten up to the ridge.

Start at the bottom right hand side and work from right to left. Use 4 nails or screws fix each shingle tile to the roof batten. If possible, use the cut-off from the previous to start the next course. Hook nose of upper tile into lip of tile below ensuring a tight fit. Continue with each successive course up.

At the upper course, cut the tiles to suit the ridge and attach a batten on top of the Shingle tile. Finally fix the ridge to the batten.

More information about the installation?

Please contact your dealer.

Accessories of the Shingle

Metrotile offers the accessories that fully integrate with the Metrotile Shingle profile.

Shingle barge board cover and gutter



For closing the edges at the side of a Metrotile Shingle roof.

| | |
|-----------------|---------|
| Overall length: | 1355 mm |
| Cover length: | 1345 mm |
| Cover width: | 118 mm |
| Depth: | 20 mm |

Shingle angle ridge



For closing the top rows of shingle tiles.

| | |
|-----------------|---------|
| Overall length: | 1355 mm |
| Cover length: | 1345 mm |
| Cover width: | 160 mm |

Shingle starter profile



A starter profile to fix the first row of shingle tiles.

| | |
|-----------------|---------|
| Overall length: | 1355 mm |
| Cover width: | 160 mm |

For a complete and detailed list of accessories and more information regarding the installation of a Metrotile roof, contact your dealer.